

## **PB-4700 JUMPER SETTING**

- **JCMOS1 : CMOS Select**  
Pin 1-2 Short : Normal  
Pin 2-3 Short : Clear CMOS
- **JCOM\_SEL1 : COM1/COM2 Port DCD/12V Output Select**  
Pin 1-3 Short : COM1 Pin1 connected to 12V  
Pin 3-5 Short : COM1 Pin1 connected to DCD  
Pin 2-4 Short : COM2 Pin1 connected to 12V  
Pin 4-6 Short : COM2 Pin1 connected to DCD
- **JCOM\_SEL2 : COM3/COM4 Port DCD/12V Output Select**  
Pin 1-3 Short : COM3 Pin1 connected to 12V  
Pin 3-5 Short : COM3 Pin1 connected to DCD  
Pin 2-4 Short : COM4 Pin1 connected to 12V  
Pin 4-6 Short : COM4 Pin1 connected to DCD
- **JCR\_SEL1 : CR Port Open/Close Status Select**  
Pin 1-3 、 2-4 Short : For COM1  
Pin 3-5 、 4-6 Short : For COM5
- **COM1~COM4 +5V through BIOS ; VGA +12V through BIOS**  
Press F2 to access Chipset\PCH-IO Configuration\
  - VGA DSUB 12V : Disabled
  - COM1 DB9 5V : Disabled
  - COM2 DB9 5V : Disabled
  - COM3 DB9 5V : Disabled
  - COM4 DB9 5V : Disabled

